

DeZURIK COMPAK CYLINDER ACTUATORS SIZING SHEETS

BHP Butterfly Valves

Double-Acting

**ASME Class 150
PTFE & RTFE (TT, TI, RT, RI) Seats**

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-35	285 1960	285 1960
2.5" 65mm	CMD-35	285 1960	285 1960
3" 80mm	CMD-35	285 1960	285 1960
4" 100mm	CMD-75	285 1960	285 1960
5" 125mm	CMD-75	N/A	285 1960
	CMD-110	285 1960	N/R
6" 150mm	CMD-160	285 1960	285 1960
8" 200mm	CMD-160	N/A	285 1960
	CMD-255	285 1960	N/R

**ASME Class 150
Metal (S2) Seats**

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-35	N/A	285 1960
	CMD-50	285 1960	N/R
2.5" 65mm	CMD-75	285 1960	285 1960
3" 80mm	CMD-75	N/A	285 1960
	CMD-110	285 1960	N/R
4" 100mm	CMD-160	285 1960	285 1960
6" 150mm	CMD-255	N/A	285 1960
	CMD-400	285 1960	N/R
8" 200mm	CMD-400	N/A	285 1960
	CMD-500	285 1960	N/R

**ASME Class 150, Dual
(TTS2, TIS2, RTS2, RIS2) Seats**

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-35	285 1960	285 1960
2.5" 65mm	CMD-35	285 1960	285 1960
3" 80mm	CMD-35	N/A	285 1960
	CMD-50	285 1960	N/R
4" 100mm	CMD-50	N/A	285 1960
	CMD-75	285 1960	N/R
6" 150mm	CMD-160	N/A	285 1960
	CMD-255	285 1960	N/R
8" 200mm	CMD-255	N/A	285 1960
	CMD-400	285 1960	N/R

N/A = Not Available. Use next larger actuator.
 N/R = Not Required. Use next smaller actuator.

BHP Butterfly Valves

Double-Acting

ASME Class 300

PTFE & RTFE (TT, TI, RT, RI) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-35	740 5100	740 5100
	CMD-35	740 5100	740 5100
3" 80mm	CMD-35	740 5100	740 5100
	CMD-75	740 5100	740 5100
5" 125mm	CMD-75	N/A	740 5100
	CMD-110	740 5100	N/R
6" 150mm	CMD-160	N/A	740 5100
	CMD-255	740 5100	N/R
8" 200mm	CMD-255	N/A	740 5100
	CMD-400	740 5100	N/R

N/A = Not Available. Use next larger actuator.
N/R = Not Required. Use next smaller actuator.

ASME Class 300

Metal (S2) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-50	N/A	740 5100
	CMD-75	740 5100	N/R
2.5" 65mm	CMD-75	N/A	740 5100
	CMD-110	740 5100	N/R
3" 80mm	CMD-110	N/A	740 5100
	CMD-160	740 5100	N/R
4" 100mm	CMD-255	740 5100	740 5100
	CMD-400	N/A	740 5100
6" 150mm	CMD-500	740 5100	N/R
	CMD-550	N/A	740 5100
8" 200mm	CMD-600	740 5100	N/R

ASME Class 300, Dual

(TTS2, TIS2, RTS2, RIS2) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-35	740 5100	740 5100
	CMD-35	740 5100	740 5100
3" 80mm	CMD-75	740 5100	740 5100
	CMD-75	N/A	740 5100
4" 100mm	CMD-110	740 5100	N/R
	CMD-400	740 5100	740 5100
6" 150mm	CMD-400	740 5100	740 5100
	CMD-400	740 5100	740 5100

Spring-to-Close

ASME Class 150

PTFE & RTFE (TT, TI, RT, RI) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-50-S8-R	285 1960	285 1960
	CMD-75-S8-R	285 1960	285 1960
3" 80mm	CMD-75-S10-R	N/A	285 1960
	CMD-110-S7-R	285 1960	N/R
4" 100mm	CMD-160-S9-R	N/A	285 1960
	CMD-255-S7-R	285 1960	N/R
5" 125mm	CMD-160-S11-R	N/A	285 1960
	CMD-255-S7-R	285 1960	N/R
6" 150mm	CMD-400-S9-R	N/A	285 1960
	CMD-500-S7-R	285 1960	N/R
8" 200mm	CMD-400-S11-R	N/A	285 1960
	CMD-500-S7-R	285 1960	N/R

N/A = Not Available. Use next larger actuator.
N/R = Not Required. Use next smaller actuator.

ASME Class 150

Metal (S2) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-75-S12-R	N/A	285 1960
	CMD-110-S8-R	285 1960	N/R
2.5" 65mm	CMD-160-S9-R	N/A	285 1960
	CMD-255-S7-R	285 1960	N/R
3" 80mm	CMD-160-S11-R	N/A	285 1960
	CMD-255-S7-R	285 1960	N/R
4" 100mm	CMD-400-S8-R	285 1960	285 1960
	CMD-500-S9-R	N/A	285 1960
6" 150mm	CMD-550-S7-R	285 1960	N/R
	CMD-550-S10-R	N/A	285 1960
8" 200mm	CMD-600-S8-R	285 1960	N/R

ASME Class 150, Dual

(TTS2, TIS2, RTS2, RIS2) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-75-S8-R	285 1960	285 1960
	CMD-75-S8-R	285 1960	285 1960
3" 80mm	CMD-75-S10-R	N/A	285 1960
	CMD-110-S7-R	285 1960	N/R
4" 100mm	CMD-160-S8-R	285 1960	285 1960
	CMD-400-S9-R	N/A	285 1960
6" 150mm	CMD-500-S7-R	285 1960	N/R
	CMD-500-S9-R	N/A	285 1960
8" 200mm	CMD-550-S8-R	285 1960	N/R

BHP Butterfly Valves

Spring-to-Close

ASME Class 300
PTFE & RTFE (TT, TI, RT, RI) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-75-S8-R	740 5100	740 5100
	CMD-75-S9-R	N/A	740 5100
2.5" 65mm	CMD-110-S7-R	740 5100	N/R
	CMD-75-S10-R	N/A	740 5100
3" 80mm	CMD-110-S7-R	740 5100	N/R
	CMD-160-S9-R	N/A	740 5100
4" 100mm	CMD-255-S7-R	740 5100	N/R
	CMD-255-S8-R	N/A	740 5100
5" 125mm	CMD-400-S7-R	740 5100	N/R
	CMD-400-S11-R	N/A	740 5100
6" 150mm	CMD-500-S7-R	740 5100	N/R
	CMD-500-S9-R	N/A	740 5100
8" 200mm	CMD-550-S8-R	740 5100	N/R

ASME Class 300
Metal (S2) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-110-S10-R	N/A	740 5100
	CMD-160-S9-R	740 5100	N/R
2.5" 65mm	CMD-255-S9-R	N/A	740 5100
	CMD-400-S7-R	740 5100	N/R
3" 80mm	CMD-255-S10-R	N/A	740 5100
	CMD-400-S7-R	740 5100	N/R
4" 100mm	CMD-500-S8-R	740 5100	740 5100
	CMD-600-S9-R	N/A	740 5100
6" 150mm	CMD-650-S8-R	740 5100	N/R
	CMD-700-S9-R	740 5100	740 5100

ASME Class 300, Dual
(TTS2, TIS2, RTS2, RIS2) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-75-S10-R	N/A	740 5100
	CMD-110-S7-R	740 5100	N/R
2.5" 65mm	CMD-75-S10-R	N/A	740 5100
	CMD-110-S7-R	740 5100	N/R
3" 80mm	CMD-160-S9-R	N/A	740 5100
	CMD-255-S7-R	740 5100	N/R
4" 100mm	CMD-255-S9-R	N/A	740 5100
	CMD-400-S7-R	740 5100	N/R
6" 150mm	CMD-550-S8-R	740 5100	740 5100
	CMD-550-S9-R	N/A	740 5100
8" 200mm	CMD-600-S8-R	740 5100	N/R

N/A = Not Available. Use next larger actuator.
N/R = Not Required. Use next smaller actuator.

Spring-to-Open

ASME Class 150
PTFE & RTFE (TT, TI, RT, RI) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-50-S8-D	285 1960	285 1960
	CMD-75-S8-D	285 1960	285 1960
3" 80mm	CMD-75-S12-D	N/A	285 1960
	CMD-110-S8-D	285 1960	N/R
4" 100mm	CMD-160-S12-D	N/A	285 1960
	CMD-255-S8-D	285 1960	N/R
5" 125mm	CMD-160-S12-D	N/A	285 1960
	CMD-255-S8-D	285 1960	N/R
6" 150mm	CMD-400-S12-D	N/A	285 1960
	CMD-500-S8-D	285 1960	N/R
8" 200mm	CMD-400-S12-D	N/A	285 1960
	CMD-500-S8-D	285 1960	N/R

ASME Class 150
Metal (S2) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-75-S12-D	N/A	285 1960
	CMD-110-S8-D	285 1960	N/R
2.5" 65mm	CMD-160-S12-D	N/A	285 1960
	CMD-255-S8-D	285 1960	N/R
3" 80mm	CMD-160-S12-D	N/A	285 1960
	CMD-255-S8-D	285 1960	N/R
4" 100mm	CMD-400-S8-D	285 1960	285 1960
	CMD-500-S12-D	N/A	285 1960
6" 150mm	CMD-550-S8-D	285 1960	N/R
	CMD-550-S12-D	N/A	285 1960
8" 200mm	CMD-600-S8-D	285 1960	N/R

ASME Class 150, Dual
(TTS2, TIS2, RTS2, RIS2) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-75-S8-D	285 1960	285 1960
	CMD-75-S8-D	285 1960	285 1960
3" 80mm	CMD-75-S12-D	N/A	285 1960
	CMD-110-S8-D	285 1960	N/R
4" 100mm	CMD-160-S8-D	285 1960	285 1960
	CMD-400-S12-D	N/A	285 1960
6" 150mm	CMD-500-S8-D	285 1960	N/R
	CMD-500-S12-D	N/A	285 1960
8" 200mm	CMD-500-S8-D	285 1960	N/R

N/A = Not Available. Use next larger actuator.
N/R = Not Required. Use next smaller actuator.

BHP Butterfly Valves

Spring-to-Open

ASME Class 300

PTFE & RTFE (TT, TI, RT, RI) Seats

ASME Class 300

Metal (S2) Seats

ASME Class 300, Dual

(TTS2, TIS2, RTS2, RIS2) Seats

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-50-S8-D	740	740
		5100	5100
2.5" 65mm	CMD-75-S8-D	740	740
		5100	5100
3" 80mm	CMD-75-S12-D	N/A	740 5100
	CMD-110-S8-D	740 5100	N/R
4" 100mm	CMD-160-S12-D	N/A	740 5100
	CMD-255-S8-D	740 5100	N/R
5" 125mm	CMD-160-S12-D	N/A	740 5100
	CMD-255-S8-D	740 5100	N/R
6" 150mm	CMD-400-S12-D	N/A	740 5100
	CMD-500-S8-D	740 5100	N/R
8" 200mm	CMD-400-S12-D	N/A	740 5100
	CMD-500-S8-D	740 5100	N/R

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-110-S8-D	N/A	740 5100
	CMD-160-S8-D	740 5100	N/R
2.5" 65mm	CMD-255-S12-D	N/A	740 5100
	CMD-400-S8-D	740 5100	N/R
3" 80mm	CMD-255-S12-D	N/A	740 5100
	CMD-400-S8-D	740 5100	N/R
4" 100mm	CMD-500-S8-D	740 5100	740 5100
	CMD-600-S12-D	N/A	740 5100
6" 150mm	CMD-650-S8-D	740 5100	N/R
	CMD-700-S9-D	740 5100	740 5100

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
2" 50mm	CMD-75-S12-D	N/A	740 5100
	CMD-110-S8-D	740 5100	N/R
2.5" 65mm	CMD-75-S12-D	N/A	740 5100
	CMD-110-S8-D	740 5100	N/R
3" 80mm	CMD-160-S12-D	N/A	740 5100
	CMD-255-S8-D	740 5100	N/R
4" 100mm	CMD-255-S12-D	N/A	740 5100
	CMD-400-S8-D	740 5100	N/R
6" 150mm	CMD-550-S8-D	740 5100	740 5100
	CMD-550-S12-D	N/A	740 5100
8" 200mm	CMD-600-S8-D	740 5100	N/R

N/A = Not Available. Use next larger actuator.
N/R = Not Required. Use next smaller actuator.

BOS-CL Butterfly Valves

Double-Acting

Valve Size	Order Code	Maximum Shutoff Pressure Differential
		Air Supply psi/kPa
		50 psi 340 kPa
1.5-2.5" 40-60mm	CMD-35	200
		1380
3" 80mm	CMD-35	100 690
	CMD-50	200 1380
4" 100mm	CMD-75	200 1380
5" 125mm	CMD-160	200 1380
6" 150mm	CMD-160	200 1380

N/A = Not Available. Use next larger actuator.
N/R = Not Required. Use next smaller actuator.

PEC Eccentric Plug Valves*

Double-Acting

Direct Pressure, Resilient Plug, Metal Seat

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
.5-1" 15 - 25mm	CMD-35	275 1890	275 1890
	CMD-50	275 1890	N/R
1.25-1.5" 32-40mm	CMD-35	225 1550	275 1890
	CMD-50	275 1890	N/R
	CMD-75	275 1890	N/R
2" 50mm	CMD-35	N/A	100 690
	CMD-50	125 860	275 1890
	CMD-75	275 1890	N/R
2.5" 65mm	CMD-50	25 170	100 690
	CMD-75	150 1030	250 1720
	CMD-110	275 1890	275 1890
3" 80mm	CMD-50	N/A	50 340
	CMD-75	50 340	125 860
	CMD-110	150 1030	250 1720
	CMD-160	275 1890	275 1890

Direct Pressure, Soft Rubber Lined Valves CIS or DIS

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
3" 80mm	CMD-75	N/A	75 520
	CMD-110	75 520	175 1210
	CMD-160	200 1380	275 1890
	CMD-255	275 1890	N/R

Reverse Pressure, Soft Rubber Lined Valves CIS or DIS

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
3" 80mm	CMD-110	N/A	75 520
	CMD-160	75 520	175 1210
	CMD-255	225 1550	275 1890
	CMD-400	275 1890	N/R

Direct Pressure, Metal Plug, Metal Seat or Hard Rubber Lined (CIH) Reverse Pressure, Resilient Plug, Metal Seat Reverse Pressure, Metal Plug, Metal Seat or Hard Rubber Lined (CIH)

Valve Size	Order Code	Maximum Shutoff Pressure Differential	
		Air Supply psi/kPa	
		60 psi 410 kPa	80 psi 550 kPa
.5-1" 15-25mm	CMD-35	225 1550	275 1890
	CMD-50	275 1890	N/R
1.25-1.5" 32-40mm	CMD-35	100 690	200 1380
	CMD-50	275 1890	275 1890
2" 50mm	CMD-50	100 690	225 1550
	CMD-75	250 1720	275 1890
	CMD-110	275 1890	N/R
2.5" 65mm	CMD-50	N/A	50 340
	CMD-75	50 340	150 1030
	CMD-110	175 1210	275 1890
	CMD-160	275 1890	N/R
3" 80mm	CMD-50	N/A	25 170
	CMD-75	25 170	75 520
	CMD-110	75 520	175 1210
	CMD-160	200 1380	275 1890
	CMD-255	275 1890	N/R

N/A = Not Available. Use next larger actuator.
N/R = Not Required. Use next smaller actuator.

Direct pressure = flow into back of plug.
Reverse pressure = flow into face of plug.

* The valve assembly pressure rating is the pressure rating of the valve or actuator, whichever is lowest.

PEC Eccentric Plug Valves*

Direct Pressure, Metal Plug, Metal Seat or Hard Rubber Lined (CIH)
Reverse Pressure, Resilient Plug, Metal Seat

Direct Pressure, Resilient Plug, Metal Seat

Reverse Pressure, Metal Plug, Metal Seat or Hard Rubber Lined (CIH)

Valve Size	Order Code		Maximum Shutoff Pressure Differential	
			Air Supply psi/kPa	
	Spring-to-Close	Spring-to-Open	60 psi 410 kPa	80 psi 550 kPa
.5-1" 15-25mm	CMD-35-S8-R	CMD-35-S8-D	N/A	<u>100</u> 690
	CMD-50-S8-R	CMD-50-S8-D	<u>200</u> 1380	N/A
	CMD-50-S12-R	CMD-50-S12-D	N/A	<u>275</u> 1890
	CMD-75-S8-R	CMD-75-S8-D	<u>275</u> 1890	N/R
1.25-1.5" 32-40mm	CMD-35-S8-R	CMD-35-S8-D	N/A	<u>25</u> 170
	CMD-50-S8-R	CMD-50-S8-D	<u>100</u> 690	N/A
	CMD-50-S12-R	CMD-50-S12-D	N/A	<u>150</u> 1030
	CMD-75-S8-R	CMD-75-S8-D	<u>150</u> 1030	N/A
	CMD-75-S12-R	CMD-75-S12-D	N/A	<u>225</u> 1550
	CMD-110-S8-R	CMD-110-S8-D	<u>250</u> 1720	N/A
	CMD-110-S12-R	CMD-110-S12-D	N/A	<u>275</u> 1890
	CMD-160-S8-R	CMD-160-S8-D	<u>275</u> 1890	N/R
2" 50mm	CMD-50-S12-R	CMD-50-S12-D	N/A	<u>25</u> 170
	CMD-75-S8-R	CMD-75-S8-D	<u>25</u> 170	N/A
	CMD-75-S12-R	CMD-75-S12-D	N/A	<u>100</u> 690
	CMD-110-S8-R	CMD-110-S8-D	<u>100</u> 690	N/A
	CMD-110-S12-R	CMD-110-S12-D	N/A	<u>200</u> 1380
	CMD-160-S8-R	CMD-160-S8-D	<u>200</u> 1380	N/A
	CMD-160-S12-R	CMD-160-S12-D	N/A	<u>275</u> 1890
	CMD-255-S8-R	CMD-255-S8-D	<u>275</u> 1890	N/R
2.5" 65mm	CMD-110-S12-R	CMD-110-S12-D	N/A	<u>25</u> 170
	CMD-160-S8-R	CMD-160-S8-D	<u>50</u> 340	N/A
	CMD-160-S12-R	CMD-160-S12-D	N/A	<u>150</u> 1030
	CMD-255-S8-R	CMD-255-S8-D	<u>175</u> 1210	N/A
	CMD-255-S12-R	CMD-255-S12-D	N/A	<u>275</u> 1890
	CMD-400-S8-R	CMD-400-S8-D	<u>275</u> 1890	N/R
3" 80mm	CMD-160-S12-R	CMD-160-S12-D	N/A	<u>75</u> 520
	CMD-255-S8-R	CMD-255-S8-D	<u>75</u> 520	N/A
	CMD-255-S12-R	CMD-255-S12-D	N/A	<u>175</u> 1210
	CMD-400-S8-R	CMD-400-S8-D	<u>175</u> 1210	N/A
	CMD-400-S12-R	CMD-400-S12-D	N/A	<u>275</u> 1720
	CMD-500-S8-R	CMD-500-S8-D	<u>275</u> 1720	N/R

Valve Size	Order Code		Maximum Shutoff Pressure Differential	
			Air Supply psi/kPa	
	Spring-to-Close	Spring-to-Open	60 psi 410 kPa	80 psi 550 kPa
.5-1" 15-25mm	CMD-35-S8-R	CMD-35-S8-D	N/A	<u>100</u> 690
	CMD-50-S8-R	CMD-50-S8-D	<u>150</u> 1030	N/A
	CMD-50-S12-R	CMD-50-S12-D	N/A	<u>225</u> 1550
	CMD-75-S8-R	CMD-75-S8-D	<u>200</u> 1380	N/A
	CMD-75-S12-R	CMD-75-S12-D	N/A	<u>275</u> 1890
	CMD-110-S8-R	CMD-110-S8-D	<u>275</u> 1890	N/R
1.25-1.5" 32-40mm	CMD-35-S12-R	CMD-35-S12-D	N/A	<u>25</u> 170
	CMD-50-S8-R	CMD-50-S8-D	<u>50</u> 340	N/A
	CMD-50-S12-R	CMD-50-S12-D	N/A	<u>100</u> 690
	CMD-75-S8-R	CMD-75-S8-D	<u>100</u> 690	N/A
	CMD-75-S12-R	CMD-75-S12-D	N/A	<u>150</u> 1030
	CMD-110-S8-R	CMD-110-S8-D	<u>175</u> 1210	N/A
	CMD-110-S12-R	CMD-110-S12-D	N/A	<u>275</u> 1890
	CMD-160-S8-R	CMD-160-S8-D	<u>275</u> 1890	N/R
2" 50mm	CMD-75-S12-R	CMD-75-S12-D	N/A	<u>25</u> 170
	CMD-110-S8-R	CMD-110-S8-D	<u>25</u> 170	N/A
	CMD-110-S12-R	CMD-110-S12-D	N/A	<u>100</u> 690
	CMD-160-S8-R	CMD-160-S8-D	<u>100</u> 690	N/A
	CMD-160-S12-R	CMD-160-S12-D	N/A	<u>200</u> 1380
	CMD-255-S8-R	CMD-255-S8-D	<u>275</u> 1890	N/A
	CMD-255-S12-R	CMD-255-S12-D	N/R	<u>275</u> 1890
	CMD-110-S12-R	CMD-110-S12-D	N/A	<u>25</u> 170
2.5" 65mm	CMD-160-S8-R	CMD-160-S8-D	<u>25</u> 170	N/A
	CMD-160-S12-R	CMD-160-S12-D	N/A	<u>50</u> 340
	CMD-255-S8-R	CMD-255-S8-D	<u>100</u> 690	N/A
	CMD-255-S12-R	CMD-255-S12-D	N/A	<u>200</u> 1380
	CMD-400-S8-R	CMD-400-S8-D	<u>175</u> 1210	N/A
	CMD-400-S12-R	CMD-400-S12-D	N/A	<u>275</u> 1890
	CMD-500-S8-R	CMD-500-S8-D	<u>275</u> 1720	N/R
	CMD-160-S12-R	CMD-160-S12-D	N/A	<u>25</u> 170
3" 80mm	CMD-255-S8-R	CMD-255-S8-D	<u>25</u> 170	N/R
	CMD-255-S12-R	CMD-255-S12-D	N/A	<u>100</u> 690
	CMD-400-S8-R	CMD-400-S8-D	<u>75</u> 520	N/A
	CMD-400-S12-R	CMD-400-S12-D	N/A	<u>175</u> 1210
	CMD-500-S8-R	CMD-500-S8-D	<u>275</u> 1890	N/A
	CMD-500-S12-R	CMD-500-S12-D	N/R	<u>275</u> 1720

N/A = Not Available. Use next larger actuator.
N/R = Not Required. Use next smaller actuator.

Direct pressure = flow into back of plug.
Reverse pressure = flow into face of plug.

* The valve assembly pressure rating is the pressure rating of the valve or actuator, whichever is lowest.

PEC Eccentric Plug Valves*

Spring-Return

Direct Pressure, Soft Rubber Lined Valves CIS or DIS

Valve Size	Order Code		Maximum Shutoff Pressure Differential	
			Air Supply psi/kPa	
	Spring-to-Close	Spring-to-Open	60 psi 410 kPa	80 psi 550 kPa
3" 80mm	CMD-255-S12-R	CMD-255-S12-D	N/A	$\frac{100}{690}$
	CMD-400-S8-R	CMD-400-S8-D	$\frac{75}{520}$	N/A
	CMD-400-S12-R	CMD-400-S12-D	N/A	$\frac{175}{1210}$
	CMD-500-S8-R	CMD-500-S8-D	$\frac{275}{1890}$	N/A
	CMD-500-S12-R	CMD-500-S12-D	N/R	$\frac{275}{1720}$

Reverse Pressure, Soft Rubber Lined Valves CIS or DIS

Valve Size	Order Code		Maximum Shutoff Pressure Differential	
			Air Supply psi/kPa	
	Spring-to-Close	Spring-to-Open	60 psi 410 kPa	80 psi 550 kPa
3" 80mm	CMD-400-S8-R	CMD-400-S8-D	$\frac{25}{170}$	N/A
	CMD-400-S12-R	CMD-400-S124-D	N/A	$\frac{75}{520}$
	CMD-500-S8-R	CMD-500-S8-D	$\frac{225}{1550}$	N/A
	CMD-500-S12-R	CMD-500-S12-D	N/A	$\frac{275}{1890}$

N/A = Not Available. Use next larger actuator.
N/R = Not Required. Use next smaller actuator.

Direct pressure = flow into back of plug.
Reverse pressure = flow into face of plug.

* The valve assembly pressure rating is the pressure rating of the valve or actuator, whichever is lowest.

Sales and Service

For information about our worldwide locations, approvals, certifications and local representative:

Web Site: DeZURIK.com E-Mail: info@DeZURIK.com



250 Riverside Ave. N. Sartell, Minnesota 56377 • Phone: 320-259-2000 • Fax: 320-259-2227

DeZURIK, Inc. reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing by DeZURIK, Inc. Certified drawings are available upon request.